

PRODUCT CODE:
30993M-BL-WH

**DYNAMIC TOWER 3.0 KIT - BLUE AND WHITE, POWDER
COATED GALVANIZED STEEL**

URBAN



DEVICE DATA

PROJECTION AND VIEW OF THE DEVICE

The device is difficult to access

Compliance with the PN-EN standard: 1176-1:2024-03

Number of users : 25

Age group : +5

Width : 2.20 m

Length : 5.90 m



Height : 2.75 m

Minimum space required : 9.82 m x 5.68 m

Free fall height : 2.20 m

Fall area : 39.78 m²

Foundation depth : -0.60 m



COMPONENTS

Single tower without roof, platform height 30 cm: 1 pc.

Single tower without roof, platform height 60 cm: 3 pcs.

Single tower without roof, platform height 100 cm: 1 pc.

Single tower without roof, platform height 120 cm: 1 pc.

Single tower without roof, platform height 150 cm: 2 pcs.

Single tower without roof, platform height 190 cm: 1 pc.

Vertical ladder: 6 pcs.

Fireman's pole, height 136 cm: 1 pc.

Fireman's pipe with ladder: 1 pc.

Plexiglass climbing wall, height 220 cm: 1 pc.

Slide height 150 cm: 1 pc.

Barrier with applications: 3 pcs.

TECHNOLOGY

Structural legs: square steel profiles, cross-section 80x80mm, hot-dip galvanized and powder coated

Filling and decorative elements: HDPE boards, 15mm thick, dyed throughout, solid polycarbonate boards

Platforms: waterproof plywood, 15mm thick, with an anti-slip layer in a "hexa" pattern, mounted on joists made of cross-section steel profiles 60x40mm, galvanized, unpainted

Steel elements: galvanized steel, powder coated

Slide: sides made of 15mm thick HDPE board (or 12mm thick HPL), slide made of 1.5mm thick AISI304 stainless steel sheet

Climbing wall: handles made of resin-based material attached to polycarbonate panels, mounted on joists made of 40x27mm cross-section steel profiles, galvanized, unpainted

Caps: system caps made of plastic, dimensions adapted to the mounting screws used

Foundations: wet poured foundation footings , made of concrete class at least C12/15

Due to continuous improvement of technical solutions, the presented drawings, including colors and dimensions, may differ slightly from the currently manufactured devices.

NOLMO Sp. z o. o. reserves all rights to copyright protection under the Act of 04.02.1994 on Copyright and Related Rights (Journal of Laws No. 28 item 83), in particular Articles 78 and 79 of that Act.