

PRODUCT CODE:
30997-BL-WH

**DYNAMIC TOWER 7.0 KIT - BLUE AND WHITE, POWDER
COATED GALVANIZED STEEL**

URBAN



DEVICE DATA

PROJECTION AND VIEW OF THE DEVICE

The device is difficult to access

Compliance with the PN-EN standard: 1176-1:2024-03

Number of users : 30

Age group : +3

Width : 6.95 m

Length : 8.80 m



Height : 4.25 m

Minimum space required : 12.68 mx 10.59 m

Free fall height : 2.70 m

Fall area : 74.45 m²

Foundation depth : -0.60 m



COMPONENTS

Tower without roof, platform height 0.90 m: 1 pc.

Tower without roof, platform height 0.90 and 2.70 m: 1 pc.

Tower with roof, platform height 1.50 m: 1 pc.

Tower with roof, platform height 1.85 m: 1 pc.

Tower with roof, platform height 0.60 and 2.10 m: 1 pc.

Slide height 0.90 m: 1 pc.

Slide height 1.50 m: 1 pc.

Spiral slide, height 1.85 m: 1 pc.

Climbing wall, height 0.90 m: 1 pc.

Fireman's pipe with ladder: 1 pc.

Fire pipe, height 0.60 m: 1 pc.

Inclined bridge with beams on ropes: 1 pc.

Diagonal rope tunnel: 1 pc.

Arched rope: 1 pc.

Drawing board: 1 pc.

"Connect Animals" panel: 1 pc.

Tic-Tac-Toe Game: 1 pc.

TECHNOLOGY

Structural legs: square steel profiles, cross-section 80x80mm, hot-dip galvanized and powder coated

Filling and decorative elements: HDPE boards, 15mm thick, dyed throughout, solid polycarbonate boards

Platforms: waterproof plywood , 15mm thick, with an anti-slip layer in a "hexa" pattern, mounted on joists made of

cross-section steel profiles 60x40mm, galvanized, unpainted

Steel elements: galvanized steel, powder coated

Ropes: multi-strand polypropylene, with a steel core, Ø 16mm connected with polyamide system connectors, screwed together with stainless steel screws

Slides: sides made of 15mm thick HDPE board (or 12mm thick HPL), slide made of 1.5mm thick AISI304 stainless steel sheet

Spiral slide: made of prefabricated segments, cast from polypropylene using the rotomoulding method, segments connected by means of machine screws and nuts

Climbing wall: handles made of resin-based material attached to polycarbonate panels, mounted on joists made of 40x27mm cross-section steel profiles, galvanized, unpainted

Drawing board: waterproof plywood , 15mm thick, painted with chalkboard paint

Tic-Tac-Toe: polypropylene cylinders, painted using the screen printing technique

Play Panels: maintenance-free composite elements that do not require external power supply

Caps: system caps made of plastic, dimensions adapted to the mounting screws used

Foundations: wet poured foundation footings , made of concrete class at least C12/15

Due to continuous improvement of technical solutions, the presented drawings, including colors and dimensions, may differ slightly from the currently manufactured devices.

NOLMO Sp. z o. o. reserves all rights to copyright protection under the Act of 04.02.1994 on Copyright and Related Rights (Journal of Laws No. 28 item 83), in particular Articles 78 and 79 of that Act.