PRODUCT CODE: NBZ08-0M-LM-YL-CM

FRESH 8.0 SET - LIME YELLOW, METAL BEIGE

FRESH



DEVICE DATA

PROJECTION AND VIEW OF THE DEVICE

A device with easily and hard-to-reach elements

Compliance with the PN-EN 1176-1:2024-03 standard

Number of users: 18

Age group: +2

Width: 3.33 m

Length : 4.14 m


Height: 2.50 m


Minimum space required : $7.61 \times 6.20 \text{ m}$

Free fall height: 0.90 m

Fall area: 29.63 m²

Foundation depth: -0.60m





COMPONENTS

Tower with roof, platform height 0.90 m: 2 pcs.

Triangular tower, platform height 0.60 m: 2 pcs.

Slide, height 0.90 m: 1 pc.

Fire pipe, height 0.90 m: 1 pc.

Entrance stairs, height 0.90 m: 1 pc.

Climbing wall, height 0.60 m: 1 pc.

Movable bridge: 1 pc.

Horizontal rope ladder: 1 pc.

Suspended platform: 1 pc.

Shop counter: 1 pc.

Labyrinth panel: 1 pc.

TECHNOLOGY

Structural legs: steel profiles 60x60mm, hot-dip galvanized, powder coated

System connector: A380 aluminum alloy casting

Roof elements: HDPE boards, 15 mm thick, HPL boards, 8 mm thick

Platforms: waterproof plywood , with a non-slip layer in a "hexa" pattern

Metal elements: galvanized steel, powder coated

Slide: sides made of 15mm thick HDPE board, slide made of 1.5mm thick AISI304 stainless steel sheet, fastened with Ericsson nuts

 $\textbf{Ropes:} \ \text{multi-strand polypropylene, with a steel core, } \varnothing \ 16 \text{mm} \ \text{, connected by means of polyamide system connectors}$

Technical card of the device

3

and aluminum alloy and stainless steel fittings

Climbing wall: HPL board, 8mm thick, anti-slip

Teaching panels: maintenance-free composite element

Caps: system plastic caps

Foundations: concrete class at least C12/15

Due to continuous improvement of technical solutions, the presented drawings, including colors and dimensions, may differ slightly from the currently manufactured devices.