PRODUCT CODE: LM006-LARCH

FITNESS SET - LARCH

LARX



DEVICE DATA

PROJECTION AND VIEW OF THE DEVICE

Hard-to-reach device

Compliance with the PN-EN standard: 1176-1:2024-03

Number of users: 18

Age group: +5

Width: 5.89 m

Length : 2.36 m


Height : 2.50 m


Minimum space required: 9.82 x 5.85 m

Free fall height: 2.30 m

Fall area : 44.52 ^{m2}

Foundation depth: -0.60 m





COMPONENTS

Tower without roof, platform height 1.36 m: 2 pcs.

Slide, height 1.36 m: 1 pc.

Vertical ladder: 3 pcs.

Climbing rope: 2 pcs.

Fire pipe, height 1.36 m: 1 pc.

Vertical climbing wall, height 1.36 m: 1 pc.

Vertical rope weave: 1 pc.

Somersault set double : 1 pc.

TECHNOLOGY

Structural legs: galvanized steel profiles, covered with impregnated larch boards

Anchors: steel, hot-dip galvanized

Platforms: waterproof plywood, 15mm thick, with a dark brown hexagonal anti-slip layer, mounted on joists made of 60x40mm cross-section steel profiles, galvanized, unpainted

Climbing wall: handles made of resin-based material, attached to 15mm thick waterproof plywood, with a dark brown hexa-pattern anti-slip layer

Slide: sides made of 15mm thick HDPE board, slide made of 1.5mm thick AISI304 stainless steel sheet

Roof elements: HDPE board, 15mm thick, dyed throughout

Steel elements: galvanized steel, powder coated

Ropes: multi-strand polypropylene, with a steel core, \emptyset 16mm, connected by polyamide system connectors, screwed with stainless screws

Caps: system caps made of plastic, dimensions adapted to the mounting screws used

Foundations: concrete class C 12/15 minimum

Due to continuous improvement of technical solutions, the presented drawings, including colors and dimensions, may differ slightly from the currently manufactured devices.

- 3 / 3 - **Printing date: 27.08.2025**